



Schutzvermerk DIN 34 beachten

Die Bestell-Nr. bezieht sich auf grundrierte Ausführung

bei Losflansch-Verbindungen
1 Seite um 25mm verlängert

Ø60	Bestell-Nr.	11081300											
	Ø D I.W.	57											
Ø80	s	1,5											
	R	240											
Ø100	Δ	15°											
	Gewicht in kg	0,13											
Ø120	Bestell-Nr.	11081300	11081310	11081320	11081330								
	Ø D I.W.	78	78	78	78								
Ø140	s	1	1	1	1								
	R	240	130	100	80								
Ø150	Δ	5°	15°	30°	45°								
	Gewicht in kg	0,10	0,10	0,10	0,15								
Ø175	Bestell-Nr.	11101300	12101300	11101310	12101310	11101320	12101320	11101330	12101330				
	Ø D I.W.	100	99	100	99	100	99	100	99				
Ø200	s	1	2	1	2	1	2	1	2				
	R		215		130		95		83				
Ø224	Δ		5°		15°		30°		45°				
	Gewicht in kg	0,10	0,20	0,10	0,20	0,15	0,30	0,20	0,35				
Ø250	Bestell-Nr.	11121300	12121300	13121300	11121310	12121310	13121310	11121320	12121320	13121320	11121330	12121330	13121330
	Ø D I.W.	120	119	118	120	119	118	120	119	118	120	119	118
Ø300	s	1	2	3	1	2	3	1	2	3	1	2	3
	R		295		155		110		88				
Ø350	Δ		5°		15°		30°		45°				
	Gewicht in kg	0,15	0,25	0,40	0,15	0,30	0,45	0,20	0,40	0,55	0,25	0,50	0,65
Ø400	Bestell-Nr.	11141310											
	Ø D I.W.	136											
Ø450	s	1,5											
	R	420											
Ø500	Δ	5°											
	Gewicht in kg	0,30											
Ø550	Bestell-Nr.	11151300	12151300	13151300	11151310	12151310	13151310	11151320	12151320	13151320	11151330	12151330	13151330
	Ø D I.W.	150	149	148	150	149	148	150	149	148	150	149	148
Ø600	s	1	2	3	1	2	3	1	2	3	1	2	3
	R		600		250		175		150				
Ø650	Δ		5°		15°		30°		45°				
	Gewicht in kg	0,20	0,45	0,60	0,30	0,55	0,85	0,35	0,70	1,15	0,45	0,90	1,30
Ø700	Bestell-Nr.	11171300	12171300	13171300	11171310	12171310	13171310	11171320	12171320	13171320	11171330	12171330	13171330
	Ø D I.W.	175	174	173	175	174	173	175	174	173	175	174	173
Ø750	s	1	2	3	1	2	3	1	2	3	1,5	2	3
	R		560		280		208		160				
Ø800	Δ		5°		15°		30°		45°				
	Gewicht in kg	0,30	0,55	0,80	0,40	0,75	1,10	0,50	1,05	1,55	0,90	1,20	1,86
Ø850	Bestell-Nr.	11201300	12201300	13201300	11201310	12201310	13201310	11201320	12201320	13201320	11201330	12201330	13201330
	Ø D I.W.	200	199	198	200	199	198	200	199	198	200	199	198
Ø900	s	1	2	3	1	2	3	1	2	3	1,5	2	3
	R		690		270		180		195				
Ø950	Δ		5°		15°		30°		45°				
	Gewicht in kg	0,35	0,65	1,00	0,40	0,80	1,15	0,50	1,05	1,50	1,15	1,55	2,30
Ø1000	Bestell-Nr.	11221310											
	Ø D I.W.	220											
Ø1050	s	1,5											
	R	675											
Ø1100	Δ	5°											
	Gewicht in kg	0,55											
Ø1150	Bestell-Nr.	11251300	12251300	13251300	11251310	12251310	13251310	11251320	12251320	13251320	11251330	12251330	13251330
	Ø D I.W.	250	249	248	250	249	248	250	249	248	250	249	248
Ø1200	s	1	2	3	1	2	3	1	2	3	1,5	2	3
	R		635		310		230		195				
Ø1250	Δ		5°		15°		30°		45°				
	Gewicht in kg	0,35	0,75	1,10	0,50	1,05	1,60	0,75	1,55	2,30	1,45	1,95	2,90
Ø1300	Bestell-Nr.	11301300	12301300	13301300	11301310	12301310	13301310	11301320	12301320	13301320	11301330	12301330	13301330
	Ø D I.W.	300	299	298	300	299	298	300	299	298	300	299	298
Ø1350	s	1	2	3	1	2	3	1	2	3	1,5	2	3
	R		625		310		230		205				
Ø1400	Δ		5°		15°		30°		45°				
	Gewicht in kg	0,50	0,95	1,40	0,75	1,30	2,05	1,00	1,90	2,85	1,85	2,50	3,60

Benennung

Segmente

Datum: 08.11.2010

Zeichn.-Nr. 4/70 Index 5