



Bei Losflansch-Verbindungen
 Segmente 45° - R = 1 D aus 2x22,5°
 Segmente 30° - R = 1,25 D
 Segmente 15° - R = 1,5 D
 Segmente 5° - R = 3,5 D

Schutzvermerk DIN 34 beachten

Die Bestell-Nr. bezieht sich auf grundrierte Ausführung

Ø350	Bestell-Nr.	11351300	12351300	13351300	11351310	12351310	13351310	11351320	12351320	13351320	11351330	12351330	13351330
	Ø D I.W.	350	349	348	350	349	348	350	349	348	350	349	348
	s	1,5	2	3	1,5	2	3	1,5	2	3	1,5	2	3
	Δ	5°			15°			30°			45°		
	Gewicht in kg	0,60	0,80	1,15	1,35	1,75	2,65	2,50	3,30	4,90	3,70	4,90	7,30
Ø400	Bestell-Nr.	11401300	12401300	13401300	11401310	12401310	13401310	11401320	12401320	13401320	11401330	12401330	13401330
	Ø D I.W.	399	398	396	399	398	396	399	398	396	399	398	396
	s	1,5	2	3	1,5	2	3	1,5	2	3	1,5	2	3
	Δ	5°			15°			30°			45°		
	Gewicht in kg	0,95	1,45	1,75	2,35	3,50	3,10	4,10	6,20	4,80	6,50	9,50	
Ø450	Bestell-Nr.	11451300	12451300	13451300	11451310	12451310	13451310	11451320	12451320	13451320	11451330	12451330	13451330
	Ø D I.W.	449	448	446	449	448	446	449	448	446	449	448	446
	s	1,5	2	3	1,5	2	3	1,5	2	3	1,5	2	3
	Δ	5°			15°			30°			45°		
	Gewicht in kg	1,75	2,48	2,95	4,95	4,20	5,60	8,40					12,10
Ø500	Bestell-Nr.	11501300	12501300	13501300	11501310	12501310	13501310	11501320	12501320	13501320	11501330	12501330	13501330
	Ø D I.W.	499	498	496	499	498	496	499	498	496	499	498	496
	s	1,5	2	3	1,5	2	3	1,5	2	3	1,5	2	3
	Δ	5°			15°			30°			45°		
	Gewicht in kg		1,75			5,40							
Ø560	Bestell-Nr.	12561300	13561300		12561310	13561310		12561320	13561320		12561330	13561330	
	Ø D I.W.	558	556		558	556		558	556		558	556	
	s	2	3		2	3		2	3		2	3	
	Δ	5°			15°			30°			45°		
	Gewicht in kg	1,60			4,40								18,80
Ø630	Bestell-Nr.	12631300	13631300		12631310	13631310		12631320	13631320		12631330	13631330	
	Ø D I.W.	628	626		628	626		628	626		628	626	
	s	2	3		2	3		2	3		2	3	
	Δ	5°			15°			30°			45°		
	Gewicht in kg					8,10						16,10	

Benennung

Segmente

Datum: 03/95

Zeichn.-Nr.

4/75

Index

2