



At loose-flange connection  
 Segments 30° - R = 1,25 D  
 Segments 15° - R = 1,5 D  
 Segments 5° - R = 3,5 D

Safety advice DIN 34

Article number for painted type

Ø350	Article-no.	11351300	12351300	13351300	11351310	12351310	13351310	11351320	12351320	13351320	11351330	12351330	13351330
	ØD inside	350	349	348	350	349	348	350	349	348	350	349	348
	s	1.5	2	3	1.5	2	3	1.5	2	3	1.5	2	3
	A	5°			15°			30°			45°		
	weight in kg	0.60	0.80	1.15	1.35	1.75	2.65	2.50	3.30	4.90	3.70	4.90	7.30
Ø400	Article-no.	11401300	12401300	13401300	11401310	12401310	13401310	11401320	12401320	13401320	11401330	12401330	13401330
	ØD inside	399	398	396	399	398	396	399	398	396	399	398	396
	s	1.5	2	3	1.5	2	3	1.5	2	3	1.5	2	3
	A	5°			15°			30°			45°		
	weight in kg	0.95	1.45	1.75	2.35	3.50	3.10	4.10	6.20	4.80	6.50	9.50	
Ø450	Article-no.	11451300	12451300	13451300	11451310	12451310	13451310	11451320	12451320	13451320	11451330	12451330	13451330
	ØD inside	449	448	446	449	448	446	449	448	446	449	448	446
	s	1.5	2	3	1.5	2	3	1.5	2	3	1.5	2	3
	A	5°			15°			30°			45°		
	weight in kg		1.75	2.48	2.95	4.95	4.20	5.60	8.40				12.10
Ø500	Article-no.	11501300	12501300	13501300	11501310	12501310	13501310	11501320	12501320	13501320	11501330	12501330	13501330
	ØD inside	499	498	496	499	498	496	499	498	496	499	498	496
	s	1.5	2	3	1.5	2	3	1.5	2	3	1.5	2	3
	A	5°			15°			30°			45°		
	weight in kg		1.75			5.40							
Ø560	Article-no.	12561300	13561300		12561310	13561310		12561320	13561320		12561330	13561330	
	ØD inside	558	556		558	556		558	556		558	556	
	s	2	3		2	3		2	3		2	3	
	A	5°			15°			30°			45°		
	weight in kg	1.60			4.40								18.80
Ø630	Article-no.	12631300	13631300		12631310	13631310		12631320	13631320		12631330	13631330	
	ØD inside	628	626		628	626		628	626		628	626	
	s	2	3		2	3		2	3		2	3	
	A	5°			15°			30°			45°		
	weight in kg					8.10						16.10	

Denomination

Segments

Date

03/95

Drawing-No.

4/75

Index

2